

# *Introduction to Nanophysics*

**Prof. J. Raynien Kwo**

**Department of Physics  
National Tsing Hua University**

# What is the size for a “nano” ?

One (nm) equals to 1/1000000000 ( $10^{-9}$ ) meter

$10^{-3}$  m , **Macro**

$10^{-6}$  m , **Micro**

$10^{-9}$  m , **Meso**

# R. Feymann Already Knew about this !

天下文化  
Science Culture

*By Richard P. Feynman*

## 費曼的主張



吳程遠、師明睿、尹萍、王碧 譯


The Pleasure of Finding Things Out

“ There's plenty of room at the bottom ! ”  
in 1959.

# Physicists noticed the “Nano” as early as .....

- 4th Century, Roman glassmaker: the color of glasses can be changed by mixing in metal particles
- In 1883, Films containing silver halides for photography were invented by George Eastman, founder of Koda.
- 1908, Gustay Mie first provided the explanation of the size dependence of color.
- Vision from Feynman in 1959: “There is plenty room at the bottom”, and also recognized there are plenty of nature-given nanostructures in biological systems.
- 1950-1960, small metal particles were investigated by physicists.
- 1957, Ralph Landauer realized the importance of quantum mechanics plays in devices with small scales.
- Before 1997 => **mesoscopic** (or low dimensional) physics : quantum dots, wells, wires.....are known already.

# ***Major Topics of Nanoscience and Technology***



# *What is the Nano Technology?*

- Science and Technology Down scaling to size under 100 nm:

Via “Top-down” lithographic patterning:


-- Moore’s law !

- Manipulate the atomic and molecular structures:

“Bottom-up” nano materials, growth and assembly.


Feymann: There’s plenty of room at the bottom

# *Major Driving Force pushing for Nano Technology: Due to the bottle neck in Microelectronics*




**Moore's Law :**  
**A 30% decrease in the size of printed dimensions in every two years.**

## BASIC CHIPMAKING PROCESS



*Two basic modern electronic technologies  
in Condensed Matter Physics Field*

# *Metal-Oxide-Field Effect Transistor*




*1960 Kahng and Atalla, First MOSFET*


*1970 First IC, 1 kbit, 750 khz microprocessor*

# 電子科技之基礎--MOSFET

## (metal-oxide-semiconductor field-effect transistor)




# 電子科技之基礎--磁記錄



# *Bottom-up Nano systems & Self-Assembly*

enabling of designing large molecules and nano materials




*Five major lessons  
that we have learned*

# **The First Lesson :**

# **Bulk-to-nano Transition**

# Ex: size-dependence of melting temperature




Ph. Buffat and J-P. Borel, Phys. Rev. A13, 2287 (1976)

# Ex: size-dependence of color


powered cadmium selenide

larger

smaller



## Ex: size-dependence of magnetism



A. J. Cox et al. Phys. Rev. B49, 12295 (1994)

# **The Second Lesson : The Advent of Nano Era**

- **The ability of growing the nano scale materials and structures**
- **The ability of detecting and manipulating on the nano scale.**

## **(I) Advance in thin film growth:**


Such as Molecular Beam Epitaxy, atomic layer deposition, laser MBE, etc...

- For nano electronics in metals, oxides, and semiconductors

## **(II) Detection at nano scale : STM, AFM, MFM, STEM, Cs-TEM**

- In 1982, Binning, and Rohrer in IBM invented scanning tunneling microscope (STM).
- In 1986, Binning, Quate, and Gerber invented the atomic force microscope (AFM).

# Integrated MBE Multi-chamber System




Now located in the Nano Technology Center, ITRI, Hsin Chu, Taiwan

**For Metal, Oxide and Semiconductor Films On the Nano scale**




# Scanning Tunneling Microscope (STM)





**Figure 1.10** Scanning tunneling microscope. (From C. Julian Chen, *Introduction to Scanning Tunneling Microscopy*, Oxford: Oxford University Press, 1993.)

# Scanning Tunneling Microscope (STM) – Physicist used to detect nano structures




Nature 409, 304 (2001)



# Quantum Corral

of 7.13 nm radius, 48 Fe atoms on the Cu (111) surface




This STM image shows the direct observation of standing-wave patterns in the local density of states of the Cu(111) surface. These spatial oscillations are quantum mechanical interference patterns caused by scattering of the 2D electron gas off the Fe adatoms and point defects.

# Scanning Transmission Electron Microscope Laboratory

2-Å STEM





1-Å STEM




Prof. C. H. Chen and  
Dr. M.-W. Chu  
In CCMS/NTU.

# Spherical Aberration Corrected (球面相差) Cs-STEM by C. H. Chen at CCMS, NTU




# High-Angle ADF: Si dumbbell, 1.36 Å spacing

15s exposure





60s exposure



*Drift ~1 Å/min !!*


# InGaAs/InAlAs superlattices on InP Substrate by MBE




- Determining the interface location and sharpness is easy.
- The *In*-distribution seems to be inhomogeneous in the InAlAs layer (blue arrows).
- Note that InP substrate is In-terminated (red arrow).

# Atomic Resolution STEM Imaging: Z-contrast


2-Å Electron Probe




$\text{SrTiO}_3$



Z-contrast



# **Electron Energy-Loss Spectroscopy (EELS)**



## **Coulomb Interaction**

$$v(r) = \sum_j \frac{e^2}{|r - r_j|}$$

$$= \sum_q v_q \rho_q e^{iqr}$$

, where  $\rho_q$  the electron density operator



## **Inelastic Scattering ( $\Delta E$ ) Probability**


$$\frac{d^2\sigma}{d\Omega dE} \sim \sum_f \left| \langle \psi_f | v(q) | \psi_i \rangle \right|^2 \delta(E_i - E_f - \Delta E)$$

$$\sim \frac{1}{q^4} \cdot S(\omega, q) \longrightarrow \text{X-ray}$$

$$\sim \frac{1}{q^2} \cdot \text{Im} \left[ \frac{1}{\varepsilon(\omega, q)} \right] \longrightarrow \text{EELS}$$


# Spectral Imaging at Ultimate Spatial Resolution

## Plasmonic Mapping: STEM-EELS (2-Å Probe)



M.-W. Chu *et al.*, Nano Lett. **9**, 399 (2009).

## Chemical Mapping: STEM-EDX (1-Å Probe)



M.-W. Chu *et al.*, Phys. Rev. Lett. **104**, 196101 (2010).

# The Third Lesson: The importance of Quantum Physics

# The cause for variation of scaling

- Influence of Boundary
  - Increase of proportion of boundaries
  - Existence of surface / edge modes
  - Geometrical reconstruction
- Decrease of the number of particles  
decrease of confinement, increase of perturbation
- Different scaling for different physical entity

**Quantum Effect:**


**=> Most likely to have new break through !**

# The connection of materials wave with mechanics

$h$  = Planck constant  
 $(6.626 \times 10^{-34} \text{ joule-sec})$

DeBroglie wave :

$$\lambda = h/p$$



Einstein:

$$E = h\nu = p^2/2m$$

Free electrons

自由電子:  $\lambda_{th}(300K) = 6.2\text{nm}$

Semiconductors

(半導體中  $10\text{nm} \leq \lambda \leq 100\text{nm}$ )


Atoms

原子:  $\lambda_{th}(300K) \leq 0.2\text{nm}$


Wave length

# Bulk Limit       Nano Limit

For bulk  
materials  
 $\lambda \ll L$



For nano  
materials  
 $\lambda \sim L$




# Major Qauntum Effect at the nano scale


- Interference
- Quantization
- Tunneling
- Quantum Spin

# (I) Interference


# The wonder of electron in waves



Classical mechanics




# The wave property of electrons




# Double Slit Interference of Electrons





$\sim$



## (II) Quantization

# **Confinement of the materials wave**




## **Standing Wave**




## **Quantizations**

# The Quantization of Energy


$n = 3$



$n = 2$



$n = 1$




$$\delta E \propto 1/L^2$$

$$L = \frac{n}{2} \lambda$$


$$p = \frac{h}{\lambda} = \frac{nh}{2L}$$

$$E_n = \frac{p^2}{2m} = \frac{n^2 h^2}{8mL^2}$$

# Quantum well: 1D confinement




# Quantum wire: 2 D-Confinement





SEM images of  $\text{MoO}_x$  nanowires on graphite surfaces  
Science 290, 2120-2123, (2000)


# Quantum dot: 3 D - Confinement




# Quantum Dots of various shape



Absorption in scattering  
From red to yellow



**powdered Cadmium Selenide**




# (III) Tunneling and Nano-electronics

### Classical Picture



electric field



in classical physics, the electron is repelled by an electric field as long as energy of electron is below energy level of the field


③nm

### Quantum Picture



in quantum physics, the wave function of the electron encounters the electric field, but has some finite probability of tunneling through

# Quantum Tunneling is the major effect for the failure of Transistor at nano scale







# 近來大力推動奈米科技的背景

## 來自微電子學可能遭遇瓶頸的考慮

### Moore's Law : 摩爾定律


A 30% decrease in the size of  
printed dimensions every 1.5 years.

矽晶上電子原件數每1年半會增加一倍






# Scaling Limits to CMOS Technology



Gate Oxide  $\sim$  5 Si Atoms thick !



Shrinking the junction depth  $\rightarrow$  increasing the carrier concentration



# CMOS scaling, When do we stop ?

**Reliability:** 25 / 22 / 18 / 16 Å

processing and yield issue

**Tunneling :** 15 Å


Design Issue: chosen for  $1\text{A}/\text{cm}^2$  leakage  
 $I_{\text{on}}/I_{\text{off}} \gg 1$  at 12 Å

**Bonding:**

Fundamental Issues---

- how many atoms do we need to get bulk-like properties?  
EELS -- Minimal 4 atomic layers !!
- Is the interface electronically abrupt?
- Can we control roughness?

In 1997, a gate oxide was 25 silicon atoms thick.




In 2007, a gate oxide will be 5 silicon atoms thick, if we still use  $\text{SiO}_2$

and at least 2 of those 5 atoms will be at the interfaces.



# Fundamental Materials Selection Guidelines



- Thermodynamic stability in contact with Si to 750°C and higher. (**Hubbard and Schlom**)  
**Alkaline earth oxide, IIIB, IVB oxide and rare earth oxide**
- Dielectric constant, band gap, and conduction band offset
- Defect related leakage, substantially less than  $\text{SiO}_2$  at  $t_{\text{eq}} < 1.5 \text{ nm}$
- Low interfacial state density  $D_{\text{it}} < 10^{11} \text{ eV}^{-1}\text{cm}^{-2}$
- Low oxygen diffusivity
- Crystallization temperature  $> 1000^\circ\text{C}$

$t_{\text{eq}}$  : **equivalent oxide thickness (EOT) to be under 1.0 nm**

$$t_{\text{eq}} = t_{\text{ox}} \kappa_{\text{SiO}_2} / \kappa_{\text{ox}}$$




# Basic Characteristics of Binary Oxide Dielectrics

Dielectrics	$\text{SiO}_2$	$\text{Al}_2\text{O}_3$	$\text{Y}_2\text{O}_3$	$\text{HfO}_2$	$\text{Ta}_2\text{O}_5$	$\text{ZrO}_2$	$\text{La}_2\text{O}_3$	$\text{TiO}_2$
Dielectric constant	3.9	9.0	18	20	25	27	30	80
Band gap (eV)	9.0	8.8	5.5	5.7	4.5	7.8	4.3	3.0
Band offset (eV)	3.2	2.5	2.3	1.5	1.0	1.4	2.3	1.2
Free energy of formation $\text{MO}_x + \text{Si}_2 \rightarrow \text{M} + \text{SiO}_2$ @727C, Kcal/mole of $\text{MO}_x$	-	63.4	116.8	47.6	-52.5	42.3	98.5	7.5
Stability of amorphous phase	High	High	High	Low	Low	Low	High	High
Silicide formation ?	-	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Hydroxide formation ?	-	Some	Yes	Some	Some	Some	Yes	Some
Oxygen diffusivity @950C ( $\text{cm}^2/\text{sec}$ )	$2 \times 10^{-14}$	$5 \times 10^{-25}$	?	?	?	$10^{-12}$	?	$10^{-13}$



# Integration Issues for High $\kappa$ Gate Stack



## Critical Integration Issues

- Morphology dependence of leakage  
*Amorphous vs crystalline films?*
- Interfacial structures
- Thermal stability
- Gate electrode compatibility
- Reliability


## Fundamental Limitations

- Fixed charge
- Dopant depletion in poly-Si gate
- Dopant diffusion
- Increasing field in the channel region


# Si CMOS Device Scaling – Beyond 22 nm node

## High $\kappa$ , Metal gates, and High mobility channel

1947 First Transistor



1960 First MOSFET



Metal Gate

High  $\kappa$  gate dielectric

Oxide/semiconductor interface


High mobility channel

Integration of Ge, III-V with Si

Moore's Law: The number of transistors per square inch doubles every 18 months

Shorter gate length  $L$   
Thinner gate dielectrics  $t_{ox}$

Driving force :  
High speed  
Low power consumption  
High package density






# Intel Transistor Scaling and Research Roadmap

## Transistor Scaling and Research Roadmap

90nm Node

2003



65nm Node

2005

50nm Length  
(Production)

30nm Length  
(Development)

Uniaxial  
Strain

SiGe S/D PMOS


1.2nm Ultra-thin SiO<sub>2</sub>

High-K &  
Metal-Gate  
Options

- High Performance Logic
- Low Operating Power Logic


45nm Node

2007




20nm Length  
(Development)

32nm Node  
2009




15nm Length  
(Research)

22nm Node  
2011



10nm Length  
(Research)

2015-2019  
Research



C-nanotube  
Prototype  
(Research)

Nanowire  
Prototype  
(Research)

Robert Chau, Intel, ICSICT 2004

**More non-silicon elements introduced**

# Science and Technology of Ultimate CMOS

## The Ultimate CMOS – End of road map

To achieve higher speed and lower power consumption


R&D of III-V InGaAs MOSFET state-of-art technology below 7 nm node,  
by combining advanced analysis of spectroscopy/microscopy/quantum transport/theoretical modeling




- In-situ ALD of oxide integrated with MBE
- Tailor reconstructed surface to be Ga-rich
- Controlled chemical reaction route and species



Portable UHV  
chamber for  
transfer 2" wafers  
in  $3 \times 10^{-10}$  torr for  
PES and STM  
analysis




High resolution synchrotron radiation  
photoemission spectroscopy in  
NSRRC by Dr. T.W. Pi.



RT and LT STM/STS study  
by Dr. W.W. Pi at CCMS/NTU

# Bragg Ptychography on III-V MOSFETs with gate length < 30 nm




# Tunneling-FETs offer sharper turn-on devices compared to MOSFETs

Lower VDD to lower switching energy ( $P_{active} \sim C \cdot V_{DD}^2$ )



Better performance for ultra low-power applications

## Atomic Model Prediction



A. M. Ionescu et al.,

Nature 479, 329 (2011).




H. Riel et al., IEDM 391 (2012).

# (IV) Quantum Spin

# Spin and Nano technology

**Electron Spin is the smallest unit of magnetism,  
came from Quantum Mechanics**



**Often being used for  
magnetic recording  
~30 billion market**





Well read: spintronics has dramatically increased data storage densities in hard drives.

**Spintronics  $\leftrightarrow$  Electronics**

# New generation of computer

## Computation and storage in one shot




**Fig. 7.** A schematic representation of RAM that is constructed of magnetic tunnel junctions connected together in a point contact array. The conducting wires provide current to the junctions and permit voltage measurements to be made. They also enable the manipulation of the magnetization of the elements by carrying currents both above and below the magnetic junctions to create magnetic fields.

**When turn-on,  
it is ready!**

# Artificial Superlattice

--- Matching the structural periodicity with physical length scale of **superconductivity and magnetism**


-- Modulation of physical properties



**Invention of metal molecular beam epitaxy in 1981**

-- Single crystal epitaxial superlattices with Atomically abrupt interfaces



# HCP crystal structure



- Similar crystal- chemical nature of rare earth forms coherent superlattices
- Metallic superlattice effect
  - Long range nature of the indirect exchange interaction
  - Magnetic coupling of magnetic rare earth through non – magnetic Y, Lu
  - Modulation of magnetic properties of Gd - Y Superlattices
  - Spin structure modification of Tm - Y, Dy - Y Superlattices
- 2-dimensional magnetism
- Interfacial magnetism


Spin structures of heavy rare - earths

# Neutron Diffraction Studies of the $\text{Gd}_{10}\text{-Y}_{10}$ Magnetic Superlattice Antiferromagnetically coupled below 200K



# Spin Structure Tailoring in artificial Superlattices

**Gd-Y    Dy-Y    Gd-Dy**




Year 1984-1989

# Giant Magnetoresistance (GMR)



## ❖ What is GMR?

- ❖ GMR is a very large change in electrical resistance that is observed in a ferromagnet/paramagnet multilayer structure.
- ❖ Resistance change occurs when the relative orientations of the magnetic moments in alternate ferromagnetic layers change as a function of applied field.
- ❖ The total resistance of this material is lowest when the magnetic orientations of the ferromagnetic layers are aligned, is highest when the orientations are anti-aligned.



M. N. Baibich, J. M. Broto, A. Fert, F. Nguyen Van Dau, and F. Petroff,  
*Phys. Rev. Lett.*, **61**, 2472 (1988).


# First Evidence of GMR



$H_s$  corresponds to the field at which all layer magnetizations point along the field direction.



# Spin-Valve GMR

- ❖ The simple structure of Spin-valve GMR :



- ❖ The magnetization of the top permalloy layer is free to rotate as the field is varied. The second permalloy layer is fixed due to its exchange interaction with the FeMn layer.

# GMR Spin Valve Reading Head




↳ Magnetization is stored as a “0” in one direction, and as a “1” in the other. This is the magnetic field sensed by the GMR head.

↳ When the head passes over these magnetic bits, the magnetization direction of the free layer in the head responds to the field in each bit by rotating either up or down.

↳ The resulting change in the resistance is sensed by the voltage across the GMR head (current passing through the GMR element is constant).

# Quantum behavior of ferromagnets


## - Spin as a quantum qubit



$$qubit = \alpha |0\rangle + \beta |1\rangle$$

Due to superposition  
More information!

# Tentative roadmap



**Can we take the “charge” out of Spintronics ?  
To generate pure spin current !**

## Spintronics vs Electronics

- ✓ Reducing the heat generated in traditional electronics is a major driving force for developing spintronics.
- ✓ Spin-based transistors do not strictly rely on the raising or lowering of electrostatic barriers, hence it may overcome scaling limits in charge-based transistors.
- ✓ Spin transport in semiconductors may lead to dissipationless transfer of information by pure spin currents.
- ✓ Allow computer speed and power consumption to move beyond limitations of current technologies.

# *Reliable generation of pure spin currents !*

- ✓ Spin Hall effect (2004)
- ✓ Spin Pumping (2006)
- ✓ Inverse Spin Hall effect (2006)
- ✓ Spin Seebeck effect (2008)
- ✓ Spin Caloritronics (2010)

# Major Qauntum Effect at the nano scale

- Interference
- Quantization
- Tunneling
- Quantum Spin

# **The Fourth Lesson:**


## **Innovations of**

## **nano structures and**

## **nano materials**

## **for various applications**

# Overview of Advanced Materials Laboratory



Color-selective Optical  
Switch, SPR-enhanced  
Sensor

Fuel Cells,  
Supercapacitors

High-gain Photo-detector,  
Solar Cells, Bio-sensor

SERS:  
Molecule/Bio-sensing

**Li-Chyong Chen**

Center for Condensed Matter Sciences  
National Taiwan University

# The Nano-world at CCMS-AML: a Fruitful Research Field with Technology Implications

JACS 123, 2791 (2001)

APL 81, 22 (2002)

JACS 127, 2820 (2005)

APL 88, 241905 (2006)

APL 90, 213104 (2007)

Adv. Func. Mater. 18, 938 (2008)

Small 4, 925 (2008)

Analytical Chem. 81, 36 (2009)

APL 79, 3179 (2001)

APL 81, 4189 (2002)

Adv. Func. Mater. 12, 687 (2002)

APL 86, 203119 (2005)

Chem. Mater. 17, 3749 (2005)

JACS 128, 8368 (2006)

PRB 75, 195429 (2007)

JACS 130, 3543 (2008)

Chapter 9, pp. 259-309,  
*Nanowires and nanobelts*, Z.L.  
Wang Ed., Kluwer (2004)  
Adv. Func. Mater. 16, 537 (2006)  
APL 90, 123109 (2007)  
Adv. Mater. 19, 4524 (2007)




Adv. Mater. 14, 1847 (2002)


Nature Mater. 5, 102 (2006)




Wire/Rod



Tube



Belt




Nanotip



Core-shell

APL 81, 1312 (2002)  
Nano. Lett. 3, 537 (2003)



Brush

Adv. Func. Mater. 14, 233 (2004)

Other Thin Films:

APL 86, 21911 (2005)

APL 86, 83104 (2005)

APL 86, 161901 (2005)

APL 87, 261915 (2005)

JVST B 24, 87 (2006)

APL 88, 73515 (2006)

Adv. Mater. 21, 759 (2009)

# A Color-selective Nanoswitch



## Photosensitive Gold Nanoparticle-embedded Dielectric Nanowires

M. S. Hu, et al., *Nature Materials* 5, 102-106 (2006)

### A Fast Breaking Paper

(in each individual field, only 1 was selected bimonthly among the Highly Cited Papers)

(<http://esi-topics.com/fbp/2007/august07-Li-ChyongChen.html>)




In ancient Arabian story of "Ali Baba and the Forty Thieves", the treasure is in a cave, of which the mouth is sealed by magic. It opens on the words "Open Sesame" and seals itself on the words "Close Sesame".

The nanopeapod (i.e., gold nanoparticle-embedded dielectric nanowire) will open to green light but shut for lights of other colors.

# Si Nanotips-Array and their Hetero-junctions: On-chip, IC-compatible


- \* Antireflection:  
**Broadband (uv-terahertz), Omnidirectional ( $>70^\circ$ )**
- \* Electroluminescence in ZnO/SiNTs:  
**IR emission, x10 higher; turn-on ~3V, x2 lower than film**
- \* Magneto-resistance in LSMO/SiNTs:  
**Room-temp. MR at lower bias and magnetic field**



Nature-Nanotechnology  
2 (2007) 770



Nano Letters  
9 (2009) 1839





Promising high-density memory:  
On-going

# Next-generation Energy Solution (I): Fuel Cell with Low-loading of Precious Metals

## Ultrafine Pt Nanoparticles Uniformly Dispersed on Arrayed Carbon Nanotubes with High Electrochemical Activity at Low Loading of Precious Metal

C. L. Sun, et al., *Chemistry of Materials* 17, 3749-3753 (2005)

C. H. Wang, et al., *J. Power Sources* 171, 55-62 (2007)







- Direct methanol fuel cell is promising power generator with a wide range of applications from portable electronic devices to automobiles.
- Nanotubes-Pt/Ru composites are highly efficient in loading precious metals. Only **one tenth** of metal loading, in comparison to the conventional, is needed.

## Next-generation Energy Solution (II): High-performance Supercapacitor

### Ultrafast Charging-discharging Capacitive Property of RuO<sub>2</sub> Nanoparticles on Carbon Nanotubes Using Nitrogen Incorporation

W. C. Fang, et al., *Electrochemistry Communications* 9, 239-244 (2007)

W. C. Fang, et al., *J. Electrochemical Society* 155, K15-K18 (2008)




- 4 fold increase in capacitance
- Optimal capacitance of 1380 F/g at 600 mV/s (theory: 1450 F/g)
- Output current as high as 23 mA/cm<sup>2</sup>
- Stable at high scan rate
- 10 fold increase in charge-discharge rate

# A Man-made Moth Eye

## Broadband and Quasi-omni-directional Anti-reflection Properties with Biomimetic Silicon Nanostructure

Y. F. Huang, et al., *Nature Nanotechnology* 2, 770-774 (2007) & US Patent 2005

Featured by NPG Asia Materials, March 2008




Many plants and animals have tiny surface structures that absorb certain wavelengths of light. These naturally formed nanostructures provide the colors in butterfly wings, camouflage for cicadas and enable moths to capture as much light as possible when flying at night. Now, we have created nanostructure surfaces which mimic moth eye and surpass its function in anti-reflection in that they absorb almost all incident light.

# Building a Nano-scale Bridge On-chip

## On-chip Fabrication of Well Aligned and Contact Barrier-Free GaN Nanobridge Devices with Ultrahigh Photocurrent Responsivity

R. S. Chen, et al., *Small* 4, 925-929 (2008)



- Nanowire: Naturally formed core-shell structure, 1D electron gas-like property
- On-chip process for building GaN nanobridge devices, which provide a large surface area, short transport path, and high responsivity for next-generation sensors and detectors

**The Fifth Lesson:**

**Nano photonics**

**and**


**Bio-applications**

# Nano-photonics and Plasmonics


## Near-field examination of blue-ray discs

Dr. Juen-Kai Wang, CCMS, NTU


S-SNOM setup



Near-field image of recorded disc








TEM image of recorded mark



- Scattering-type SNOM reveals sub-10 nm optical signature.
- The optical contrasts of the dark and the bright regions in near-field image of phase-change layer correspond to amorphous and polycrystalline AgInSbTe, respectively.
- Small bright spots with a size of ~30 nm emerge within the dark region, corresponding to the nano-sized ordered domains in the TEM image.
- s-SNOM provides a direct optical probe in nanometer scale for high density optical storage media.




# Creating Monodispersed Ordered Arrays of Surface-Magic-Clusters and Anodic Alumia Nanochannels by Constrained Self-organization



Prof. Yuh-Lin Wang 王玉麟  
IAMS Academia Sinica, Taiwan

# A High Sensitivity and High Speed Biomedical Diagnostic Technology with Surface Enhanced Raman Scattering (SERS)


Dr. Juen-Kai Wang, CCMS, NTU





中央研究院  
原子分子科學研究所  
Institute of Atomic and Molecular Sciences  
Academia Sinica

Prof. Yuh-Lin Wang 王玉麟  
IAMS Academia Sinica, Taiwan

# SERS detection of bacterial cell wall



Dr. Juen-Kai Wang, CCMS, NTU



- Sensitive and stable SERS profiles based on our substrates readily reflect different bacterial cell walls found in Gram-positive, Gram-negative, and mycobacteria group.
- Characteristic changes in SERS profile are recognized in the drug-sensitive bacteria to antibiotic exposure, which could be used to differentiate them from the drug-resistant ones.



# The Advent of Carbon Era ?

The Physics of Graphene:

- Possibility of relativistic electronics and spintronics

# Background for search new platform

## Scaling limit of Si MOSFET & superparamagnetism





## Carbon era?

Thompson and Parthasarathy,  
Materialstoday 9, 20, 2006


# Carbon Nanotube

- Structure of carbon nanotubes

Carbon:  $1s^2$ ,  $2s^1$      $2p^3$




# Carbon Nanotube



*Sumio Iijima*

Single-walled carbon nanotube, SWCNT



Multi-walled carbon nanotube, MWCNT


Carbon Nanotube based Transistors / Electronics

# Unexpected realization of graphene sheet

(←



mechanically exfoliated graphene sheets



AFM image of single-layer graphene on  $\text{SiO}_2$   
K.S. Novoselove et al., Science 306, 666 (2004)

# *Papers to read*

- “Observation of a Magnetic Antiphase Domain Structure with Long-Range Order in a Synthetic Gd-Y Superlattice”, C. F. Majkrzak, J. W. Cable, J. Kwo, M. Hong, D. B. McWhan, Y. Yafet, J. V. Waszczak, and C. Vettier, *Phys. Rev. Lett.* **56**, 2700, (1986).
- M. N. Baibich, J. M. Broto, A. Fert, F. Nguyen Van Dau, F. Petroff, *Phys. Rev. Lett.*, **61**, 2472 (1988).
- “High k gate dielectrics  $\text{Gd}_2\text{O}_3$  and  $\text{Y}_2\text{O}_3$  for Si”, J. Kwo\*, M. Hong, A.R. Kortan, K. T. Queeney, Y. J. Chabal, J. P. Mannaerts, T. Boone, J. J. Krajewski, A. M. Sergent, and J. M. Rosamilia, *Appl. Phys. Lett.*, **77**, 130, (2000).
- “Epitaxial Cubic  $\text{Gd}_2\text{O}_3$  as a Dielectric for GaAs Passivation”, M. Hong, J. Kwo, A. R. Kortan, J. P. Mannaerts, and A. M. Sergent, *Science*, **283**, 1897, (1999).
- “Observation of the Spin Hall Effect in Semiconductors”, Y. K. Kato, R. C. Myers, A. C. Gossard, D. D. Awschalom\*, *Science* **306**, 1910 (2004).
- “Tunnel field-effect transistors as energy-efficient electronic switches”, A. M. Ionescu, and H. Riel, *Nature*, **479**, 329 (2011).